
Yealink

Yealink SIP-T57W IP phone Grey LCD Wi-Fi

Brand : Yealink **Product code:** 1301089

Product name: SIP-T57W





Product type * IP Phone Microphone mute C722, G.723.1, G.726, G.729A, G.729A, G.729A, G.729A, G.729B, ILBC Product colour * Grey Voice codecs G.722, G.723.1, G.726, G.729A, G.729A, G.729B, ILBC Performance Adaptive jitter buffers V Dual-Tone Multi-Frequency (DTMF) modes In-band, Out-of band, SIP info modes Comfort noise generation (CNG) V Phone features V Anti-clipping (ACLP) V Answering machine V Network V Call waiting V Ethernet LAN * V Speed dialling V Ethernet LAN interface type Gigabit Ethernet Call forwarding V Ethernet LAN interface type Gigabit Ethernet Call forwarding V Wi-Fi * V Conference call V Wi-Fi standards 802.11a, 802.11b, 802.11g, Wi-Fi (802.11ac) Redialing V Supported network protocols FTP/FTP/HTTP/HTTP/HTTP/HTTP/HTTP/HTTP/HT			Audio	
Mounting Desk/Wall Voice activity detection Adaptive jitter buffers Automatic gain control Automatic gain control Comfort noise generation (CNG) Anti-clipping (ACLP) Phone features Answering machine Call waiting Automatic gain control Anti-clipping (ACLP) Packet loss concealment (PLC) Answering machine Call waiting Automatic gain control Anti-clipping (ACLP) Packet loss concealment (PLC) Answering machine Call waiting Automatic gain control Anti-clipping (ACLP) Packet loss concealment (PLC) Answering machine Call waiting Anti-clipping (ACLP) Packet loss concealment (PLC) Answering machine Call waiting Anti-clipping (ACLP) Answering machine Call waiting Anti-clipping (ACLP) Answering machine Call waiting Anti-clipping (ACLP) A	Handset type			G.722, G.723.1, G.726, G.729A,
Performance Dual-Tone Multi-Frequency (DTMF) modes Phone features Answering machine Call waiting Speed dialling Call hold Call forwarding Comfort noise generation (CNG) Anti-clipping (ACLP) Packet loss concealment (PLC) Answering machine Call waiting Speed dialling Speed dialling Call hold Vi-Fi * Call forwarding Conference call Redialing Vi-Fi standards Redialing Redialing Vi-Fi standards Redialing Vi-Fi standards Redialing Redialing Redialing Redialing Vi-Fi standards Redialing Redialing Redialing Redialing Vi-Fi standards Redialing Redialing Redialing Redialing Redialing Redialing Redialing Vi-Fi standards Redialing Redi				✓
Dual-Tone Multi-Frequency (DTMF) modes In-band, Out-of band, SIP info Mati-clipping (ACLP) Phone features Answering machine Answering machine Answering machine Answering machine Call waiting Speed dialling Call Hold Call forwarding Call forwarding Conference call Redialing Answering machine Answering machine Call sturb function Call forwarding Conference call Anound disturb function Caller ID * Phone book capacity * Call park Call park Call park Call park Anonymous call Anonymous of VolP accounts * Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Forts & interfaces Call return Anough and the standard selection Forts & interface type Anough and the standa	Performance		, ,	•
Phone features Packet loss concealment (PLC)		In-band, Out-of band, SIP info	Comfort noise generation (CNG)	
Call waiting Speed dialling Call hold Call forwarding Conference call Redialing Conference call Redialing On not disturb function Caller ID* Phonebook capacity* Call pick up Anonymous call Anonymous call Anonymous call Anonymous call Full duplex Short Message Service (SMS) Number of VoIP accounts* 16 Call return Call return Call ransfer Message-waiting indicator (MWI) Call history Ethernet LAN * Ethernet LAN * Ethernet LAN interface type Gigabit Ethernet Gigabit Ethernet Gigabit Ethernet Gigabit Ethernet Gigabit Ethernet Abv. Full ethernet LAN (R) * Security algorithms AES, HTTPS, MD5, SRTP IEEE 802.11a, IEEE 802.11ac, IE	Phone features		, , <u>-</u>	1
Speed dialling Call hold Call forwarding Conference call Redialing On to disturb function Caller ID* Very Call park	•	1	Network	
Speed dialling Call hold Call forwarding Conference call Confe	=	✓	Ethernet LAN *	1
Call hold Call forwarding Conference call Redialing Pon not disturb function Caller ID* Phonebook capacity* Call prick Call prick Call prick up Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts* 16 Call return Call transfer Message-waiting indicator (MWI) Call history Wi-Fi * Wi-Fi Wi-	· -	√	Ethernet LAN interface type	
Conference call Redialing Po not disturb function Caller ID * Phonebook capacity * Call park Call pick up Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * Call return Call return Call ristory Wi-Fi standards Bluetooth * Supported network protocols FTP/TFTP/HTTP/HTTPS AES, HTTPS, MD5, SRTP IEEE 802.11a,		√		-
Redialing	•	V	Wi Ei standards	802.11a, 802.11b, 802.11g, Wi-Fi 4
Do not disturb function Caller ID * Phonebook capacity * Call park Call pick up Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * Call return Call transfer Message-waiting indicator (MWI) Call history Supported network protocols Supported network protocols FTP/TFTP/HTTP/HTTPS AES, HTTPS, MD5, SRTP IEEE 802.11a, IEEE 802.11a, IEEE 802.11g, IEEE 802.11g, IEEE 802.11g, IEEE 802.11g, IEEE 802.11g, IEEE 802.13g IEEE 802.3af Ports & interfaces V Short Message Service (SMS) V USB 2.0 ports quantity 1 Ethernet LAN (RJ-45) ports 2 Call return Call transfer V DC-in jack Power Power Power Power Ethernet (PoE) *		V	WI-FI StalldaldS	(802.11n), Wi-Fi 5 (802.11ac)
Caller ID * Phonebook capacity * 1000 entries Security algorithms AES, HTTPS, MD5, SRTP IEEE 802.11a, IEEE 80	•	V	Bluetooth *	
Phonebook capacity * 1000 entries Call park Call park Call pick up Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * 16 Call return Call transfer Message-waiting indicator (MWI) Call history AES, HTTPS, MD5, SRTP IEEE 802.11a, IEEE 802.11g, IEEE 802.11g, IEEE 802.11n, IEEE 802.11p, IEEE 802.12p, IEEE		V	Supported network protocols	FTP/TFTP/HTTP/HTTPS
Call park Call pick up Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * Call return Call transfer Message-waiting indicator (MWI) Call history Networking standards Networking standar		1000 entries		
Call pick up Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * Call return Call transfer Message-waiting indicator (MWI) Call history Networking standards Networking standards 802.11a, IEEE 802.13 in IEEE 802	• •	1000 entries	Security algorithms	
Anonymous call Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * 16 Call return Call transfer Message-waiting indicator (MWI) Call history Networking standards 802.11n, IEEE 802.12 IEEE 802.13 ROTE ROTE ROTE ROTE ROTE ROTE ROTE ROT	·	4		
Anonymous call rejection Full duplex Short Message Service (SMS) Number of VoIP accounts * Call return Call transfer Message-waiting indicator (MWI) Call history IEEE 802.3af Ports & interfaces USB 2.0 ports quantity Ethernet LAN (RJ-45) ports RJ-9 ports quantity 2 Coll ports quantity Call by ports quantity Power Power Power over Ethernet (PoE) *		4	Networking standards	
Full duplex Short Message Service (SMS) Number of VoIP accounts * 16 Ethernet LAN (RJ-45) ports RJ-9 ports quantity Call transfer DC-in jack Message-waiting indicator (MWI) Call history Power Power over Ethernet (PoE) *	•	1		
Short Message Service (SMS) Number of VoIP accounts * 16 Ethernet LAN (RJ-45) ports 2 Call return Call transfer DC-in jack Power Call history Table 10 Call transfer Power over Ethernet (PoE) *		1	Ports & interfaces	
Number of VoIP accounts * 16 Ethernet LAN (RJ-45) ports 2 Call return	•	1	USB 2.0 ports quantity	1
Call return	-	16		
Call transfer		/	•	
Message-waiting indicator (MWI) Call history Power Power over Ethernet (PoE) *		1	· · · · ·	
Call history Power over Ethernet (PoE) *		1		•
Marian and final and		√		,
AC adapter input voitage 100 - 240 V	Management features			
Integrated voicemail ✓ AC adapter output voltage 5 V		1	· · · · =	
Volume control Buttons AC adapter output current 2 A	-		· · · · · ·	
Display Operational conditions		Buttons		
		LCD	•	0.40.95
Display LCD Operating temperature (T-T) 0 - 40 °C	• •			
Display diagonal 17.8 cm (7") Operating relative humidity (H-H) 10 - 95%				10 - 95%
Display resolution 800 x 480 pixels Weight & dimensions Touchscreen *			Weight & dimensions	
Width 259.4 mm			Width	259.4 mm
Camera Depth 220 mm	Camera			
Front camera X Height 211 mm	Front camera	X	Height	211 mm
Audio Packaging content	Audio		Packaging content	
Speakerphone * ✓ Quick start guide ✓	Speakerphone *	1	Quick start guide	1
Number of handles included * 1 pc(s)			Number of handles included *	1 pc(s)
Cables included LAN (RJ-45)			Cables included	LAN (RJ-45)





6938818303249

0841885103772



841885103772

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.