logitech



DATASHEET

RALLY BAR HUDDLE

VIDEO ENABLE HUDDLE AND SMALL ROOMS. ALL-IN-ONE VIDEO CONFERENCING AT THE TOUCH OF A BUTTON.

ALL-IN-ONE VIDEO BAR FOR HUDDLE AND SMALL ROOMS

Designed to deliver video meetings with ease, Rally Bar Huddle is quick to set up in person or remotely, simple to manage, and easy to integrate with your existing video conferencing solutions through CollabOS.

Rally Bar Huddle works with most platforms you use to connect hybrid teams, ensuring an effortless experience from the home to the office, and everywhere in between.

Combine Rally Bar Huddle with Tap IP and Tap Scheduler to make it easy to schedule, join, and participate in video meetings.

EVERYONE IS SEEN AND HEARD CLEARLY

Al video intelligence, advanced sound pickup, noise suppression, and ongoing software improvements provide a clear and natural meeting experience for remote workers.







WORKS WITH LEADING VIDEO PLATFORMS

Rally Bar Huddle works with most platforms you use to connect hybrid teams, ensuring an effortless experience from the home to the office, and everywhere in between.







QUICK TO SET UP, EASY TO MANAGE



Designed to deliver video meetings with ease, Rally Bar Huddle is quick to set up, simple to manage, and easy to integrate with Tap IP through CollabOS. Plus, use the included Multi Mount to mount Rally Bar Huddle one of three ways; on the wall, on the table, or above the display.

Plus, use Rally Bar Huddle as a meeting room appliance, in USB mode connected to a meeting room PC, or connect via laptop.







DIMENSIONS	SYSTEM REQUIREMENTS	PACKAGE CONTENTS	WARRANTY INFORMATION
Width: 549.6 mm (21.6 in) Height: 78.9 mm (3.1 in) Depth: 76.0 mm (3.0 in) Weight: 3.9 lbs (1.8 kg)	Internet Connection: Wired or wireless USB Mode: Windows® 11, Windows 10, the two most recent versions of macOS Appliance Mode: Room solution software license (not included)	Rally Bar Huddle Multi-Mount Power supply AC power cord HDMI cable USB cable	Standard: 2-year limited hardware warranty included. Extended: Additional one-year and three-year extended warranties available at the time of hardware purchase. Contact your reseller for availability.

TECHNICAL SPECIFICATIONS

Certifications and Compatibility:

For details on certifications and compatibility, visit: <u>prosupport.logi.com/hc/en-us/</u> articles/1500001344641.

General Specifications:

Built-in Components: 6 DMIC microphone array, digital PTZ camera, 1 full range ported speaker, cable management & retention system, multi functional mount, integrated motorized privacy shutter, Logitech CollabOS platform

Enclosure: All-in-one enclosure with field

replaceable front cover

Device Management: Logitech Sync

Displays Supported: 1 (2nd display support is

coming soon)

Display Resolution: Up to 1080p Network Protocol Support: IPv4, IPv6

Proxy Support: IP based Proxy, FQDN based Proxy,

Proxy using PAC file

Camera:

Digital Pan: ±48° at 4x zoom Digital Tilt: ±32° at 4x zoom Zoom: 4X HD digital zoom Diagonal Field of View: 120° Horizontal Field of View: 80° Vertical Field of View: 80° Resolution: up to 4k

Speakers:

Driver: 55 mm with bass reflex enclosure and

patented suspension design

Sensitivity: 83 dB SPL @1W +/-2dB t 1 meter Rated Power: 8WTHD: 1kHz <2% at 1W

Speaker Sampling Rate: 48KHz

Impedance: 4 Ohms

Microphones:

Frequency Response: 90Hz – 16kHz Sensitivity: -36dBFS +/-1 dB @ 1Pa Microphone data rate output: 48 kHz Pickup Range: Up to 23 ft (7m)

Beamforming Elements: Six omnidirectional digital MEMS microphones forming five adaptive

acoustic broadside beams

Audio processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector) Noise suppression: Al based de-noising algorithm

Interfaces:

HDMI Out:1 HDMI In:1

USB: 1x Type A, 1x Type C Network: 10/100/1G Ethernet WiFi: 802.11a/b/q/n/ac

Power and Cables:

Power supply: Auto-sensing

Operating Voltage/Power: 100-240V, 19V, 2.1A Power Supply Dimensions: 4.48 in (114 mm) x 1.85

in (47 mm) x 1.27 in (32.3 mm)

DC Cable: 5 ft (1.5 m) AC Cable: 4.9 ft (1 m) HDMI 1.4 Cable: 6.5 ft (2 m)

USB A to USB C 3.0 Cable: 7.2 ft (2.2 m)

Environmental:

Operating Temperature: 0 to 40°C Storage Temperature: -25 to 70°C

Humidity: 10 to 90%

Security:

File Based Encryption: AES-128 Data Encryption: Symmetric Keys, PKI

Device Identity: Protected by device attestation Device Access: Authenticated using API Key Protection: Arm TrustZone, RPMP

Accessories:

Covers: Rally Bar Huddle Front Cover-Cleanable,

Off-White Fabric

Mounts: Wall Mount for Video Bars, TV Mount for

Video Bars

Touch Controller: Logitech Tap and Tap IP

PART NUMBER

960-001485

logitech[®]

logitech.com/rallybarhuddle

Contact your reseller or contact us at logitech.com/vcsales

Logitech Americas

7700 Gateway Blvd. Newark, CA 94560 USA

Logitech Europe S.A.

EPFL - Quartier de l'Innovation Daniel Borel Innovation Center CH - 1015 Lausanne

Logitech Asia Pacific Ltd. Tel : 852-2821-5900

Fax: 852-2520-2230

© 2022 Logitech. Logitech, Logi, Rally Bar Huddle, Sync and their logos are trademarks or registered trademarks of Logitech Europe S.A. and/or its affiliates in the U.S. and other countries

Microsoft and Windows are trademarks of the Microsoft Corporation. Zoom is a trademark of Zoom Video Communications, Inc. Google Meet is a trademark of Google LLC. macOS is a trademark of Apple Inc. USB-C is a trademark of USB Implementers Forum. All other third party trademarks are the property of their respective owners.

Published June 2023