

1000 W / 850 W / 750 W / 650 W / 550 W



FOCUS GX



SPECIAL FEATURES

- High Efficiency, 80 PLUS® Gold Certified
- Fully Modular Cabling Design
- Compact Size (140 mm)
- 120 mm Fluid Dynamic Bearing (FDB) Fan
- Seasonic Hybrid Silent Fan Control
- Highly Reliable Japanese 105 °C Aluminum Electrolytic Capacitors
- Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3%]
- Cable-free Connection Design
- Multi-GPU Technology Support

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
FOCUS GX-1000	25 A	25 A	83 A	0.3 A	3 A	1000 W
FOCUS GX-850	20 A	20 A	70 A	0.3 A	3 A	850 W
FOCUS GX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
FOCUS GX-650	20 A	20 A	54 A	0.3 A	3 A	650 W
FOCUS GX-550	20 A	20 A	45 A	0.3 A	3 A	550 W



CONNECTOR QUANTITY

Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	Molex to SATA 3.3 Adapter
FOCUS GX-1000	1	2	6 (3 cables)	10	5	2
FOCUS GX-850	1	2	6 (3 cables)	10	5	2
FOCUS GX-750	1	2	4 (2 cables)	10	3	2
FOCUS GX-650	1	2	4 (2 cables)	10	3	2
FOCUS GX-550	1	2	2 (1 cables)	10	3	2

10 YEARS WARRANTY

80 PLUS GOLD

ErP Lot 6 2013 compliant

Safety & EMI / EMC CB EAC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com

www.seasonic.com