

ASUS VA27AQSB

178° Ultra-wide View with Eye Care Monitor



Low Blue Light
& Flicker Free

Key Features

WQHD
2560x1440

Supporting WQHD
2560x1440 resolution for
crystal clear image quality



IPS technology panel is
optimized for the finest image
and color quality with 178°
wide-viewing-angle

75 Hz
Refresh Rate

Decimating blurry to gain the
upper hand in current video
games



Frameless Design

Frameless, edge-to-edge
design suitable for multi
display setup



Play Like a Pro

Exclusive GamePlus function
provides the accurate and
perfect gaming experience

1ms
MPRT
Trace Free

Eliminate ghosting, allowing
you to smoothly react your
game



Flicker-free

To eliminate the disturbing
flickers on screen to
reduce eye fatigue



Ultra-low
Blue Light

Blue light filter protects you
from harmful blue light



4-way Ergonomic
Stand

With an ergonomically-
designed stand with tilt,
swivel, pivot, and height
adjustments

ASUS

Specification

Display	Panel Size : Wide Screen 27-inch (68.47 cm) LED backlight, 16:9 Display Viewing Area (HxV) : 596.74 x 335.66 mm Panel Type : WLED / IPS Display Surface : Non-glare True Resolution : WQHD 2560 x 1440 Pixel Pitch : 0.233 mm Brightness(Max) : 350 cd/m² Contrast Ratio : 1,000:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR≥10) : 178°(H)/178°(V) Color Saturation : 100% sRGB Response Time : 1ms MPRT* Display Colors : 16.7M Flicker Free : Yes	
Video Feature	Trace Free Technology : Yes SPLENDID Video Intelligence Technology : Yes SPLENDID Video Preset Modes : 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Blue Light Filter : Yes Rest Reminder : Yes Color Augmentation : Yes Color Temperature Selection : 4 Modes Skin-Tone Selection : 3 mode HDCP support: Yes, 1.4 Vivid Pixel Technology : Yes GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) QuickFit : Yes Adaptive-Sync : 48 – 75Hz Motion Sync : Yes	
Audio Feature	2W x 2, Stereo RMS	
I/O Ports	Signal Input : DisplayPort 1.2 x 1 HDMI (v1.4) x 1 USB Hub: USB 2.0 Type-A x 2 Earphone Jack : Yes (3.5mm Mini-jack) HDMI DisplayPort  USB Hub (1U, 2D) Earphone out	
Signal Frequency	Digital Signal Frequency : 24~112 KHz(H)/ 48~75 Hz(V)	
Power Consumption	Power on (Typical) : <40W Power Saving Mode : < 0.5W Power Off Mode : <0.5W Voltage : 100-240V, 50 / 60Hz	
Mechanical Design	Chassis Colors : Black Tilt : +35° ~ -5° Swivel : +180° ~ -180°	Pivot : 90° (Clockwise& Anticlockwise) Height Adjustment : 0 ~ 150 mm VESA Wall Mounting : 100 x 100 mm
Security	Kensington lock	
Dimensions	Phys. Dimension with Stand (WxHxD) : 613.83 x (367.29 ~ 517.29) x 226.3 mm Phys. Dimension without Stand (WxHxD) : 613.83 x 365.81 x 51.54 mm Box Dimension (WxHxD) : 712 x 441 x 207 mm	
Weight	Net Weight (Esti.) : 6.69 kg Net Weight without Stand (For VESA Wall Mount) (Esti.) : 4.41 kg Gross Weight (Esti.) : 8.54 kg	
Accessories	Power Cord, DisplayPort cable (optional), HDMI cable (optional), USB cable (optional), Warranty card, Quick Start Guide	
Compliance Standard	Energy Star®, UL/cUL, CB, CE, FCC, CCC, BSMI, CU, RCM, VCCI, JM, PSE, MEPS, CEC, TCO, CEL, ROHS, WEEE, PC Recycle, ISO-9241, TUV-GS, TUV-Ergo, KCC, KC, e-Standby, WHQL (Windows 10, Windows 8.1, Windows 7), TÜV-Flicker free, TÜV-Low Blue Light	

1ms MPRT spec is based on internal testes. Response time may vary depending on test conditions
Measuring a screen brightness of 200 nits without audio / USB / Card reader connection
All specifications are subject to change without notice.

