



## MeetUp



### Logitech's premier ConferenceCam designed for huddle rooms

MeetUp is Logitech's premier ConferenceCam designed for small conference rooms and huddle rooms. With a room-capturing, super-wide 120° field of view and 4K optics, MeetUp makes every seat at the table clearly visible. The integrated audio is optimised for huddle room acoustics and delivers an exceptional sound experience.

### WHAT'S IN THE BOX

- Logitech® MeetUp
- Table and wall mount
- 5-metre (16 ft) USB cable
- 2-year manufacturer's guarantee

### FEATURES

- Super-wide 120° field of view
- Ultra HD 4K image sensor
- 3-microphone and custom-tuned speaker
- Compact all-in-one design
- Razor-sharp optics



## PACKAGE SPECIFICATIONS

	Primary pack	Master shipper carton
Part #	993-001391	N/A
Bar code	5099206074859 (EAN-13)	50992060748518 (SCC-14)
Weight gr	213.6	2879.6
Length cm	20	37.6
Width cm	3.05	21.4
Height/depth cm	20.7	22.3
Volume	1.26 dm <sup>3</sup>	0.02m <sup>3</sup>
1 primary pack	1	N/A
1 master shipper carton	12	1
1 pallet EURO	840	70
1 container 20 ft	12480	1040
1 container 40 ft	26208	2184
1 container 40 ft HQ	26208	2184

## SYSTEM REQUIREMENTS

- Windows® 7, Windows 8.1 or Windows 10
- Mac OS X 10.10 or higher
- Google Chromebook Version 29.0.1547.70, Platform 4319.79.0 with:
- 2.4 GHz Intel® Core 2 Duo processor
- 2 GB RAM or more
- USB 2.0 port (USB 3.0 required for 4k video)

## TECHNICAL SPECS

- Super-wide 120° field of view
- 3-microphone speakerphone
- Optional wireless expansion microphone-ready
- 4K Ultra HD video calling (up to 3840 x 2160 pixels @ 30 fps); 1080p Full HD video calling (up to 1920 x 1080 pixels @ 30 fps); 720p HD video calling (up to 1280 x 720 pixels @ 30 fps) with supported clients
- All-in-one design
- Motorised pan/tilt
- Logitech-engineered lens
- 3 camera presets
- Bluetooth® wireless technology
- RF remote control
- Plug-and-play USB connectivity
- Works with most video conferencing applications
- Certified for Business
- Multiple mounting options (includes table and wall mount; optional TV mount available)
- Kensington security slot
- 5-metre (16 ft) USB cable

### Microphone:

- Sensitivity: •27 dB
- Microphone frequency response: 90 Hz • 16 kHz for full voice reproduction and high intelligibility without noise
- Factory paired, very low distortion broadside beamforming algorithm steers the microphones directly at the talker for the best voice pickup and noise reduction

### Speaker:

- Powerful rare-earth magnet
- Acoustically suspended speaker enclosure
- Volume adjustable to 95 dB SPL at 0.5 metre peak
- Speaker sensitivity 86.5+/-3dB SPL at 0.5 metre
- Distortion: 200 Hz•0.300 Hz < 3%, 3000 Hz•0.10 kHz < 1%
- Peak-limiting algorithm prevents even momentary speaker clipping without distortion
- Acoustic echo cancellation
- VAD (Voice activity detector)
- Microphone background noise suppression
- Pro-audio 32 kHz sampling rate

### Main unit:

- 400 mm x 104 mm x 85 mm (15.75" x 4.1" x 3.35")
- 1.04 kg (2.3 lbs)

### Remote:

- 83 mm x 10 mm x 83 mm (3.25 x 0.375 x 3.25")
- 72 g (2.5 oz)