logitech®

Rally Bar

Rally Bar is Logitech's premier, all-in-one video bar for mid-sized meeting rooms. With brilliant optics, powerful audio, and adaptive AI- driven performance, Rally Bar sets a new standard for video collaboration. Deploy Rally Bar at scale with exceptional flexibility and ease.

WHAT'S IN THE BOX

Rally Bar
Power supply
AC power cord
HDMI cable
USB cable
Lens caps
Remote control
User documentation

FEATURES

System Requirements
Internet Connection: Wired or wireless
USB Mode: Windows® 10 or later, Windows® 7 with the latest service pack, latest 2 versions of macOS

Appliance Mode: Room solution software license (not included)

logitech®

PACKAGE SPECIFICATIONS

	Primary pack	Master shipper carton
Part #	991-000424	N/A
Bar code	5099206102194 (EAN-13)	50992061021917 (SCC-14)
Weight gr	12959	12960
Length cm	100.7	101.3
Width cm	26.4	27
Height/depth cm	31.4	32.7
Volume	83.48 dm3	0.09m3
1 primary pack	1	N/A
1 master shipper carton	1	1
1 pallet EURO	10	10
1 container 20 ft	329	329
1 container 40 ft	693	693
1 container 40 ft HQ	792	792

SYSTEM REQUIREMENTS

General
Built-in Components: 6 beamforming microphones, PTZ camera, 2 speakers, AI Viewfinder, cable management & retention system, table stand, Logitech CollabOS platform
Enclosure: All-in-one enclosure with integrated table stand and patented suspension system to eliminate vibration-induced camera shake and audio interference
Device Management: Logitech Sync
Displays Supported: 2
Display Resolution: Up to 4k

Dimensions
Height: 164 mm / 6.46 in
Width: 910 mm / 2.99 ft
Depth: 130.5 mm / 5.14 in
Lens Depth: 28.8 mm / 1.13 in
Weight: 7.08 kg / 15.6 lbs

Camera
Resolution: 4K, 1440p, 1080p, 900p, 720p, and SD at 30fps
Pan: motorized ±25°
Tilt: motorized ±15°
Zoom: 15X HD zoom (5X optical, 3X digital)
Diagonal Field of View: 90°
Horizontal Field of View: 82.1°
Vertical Field of View: 52.2°
Total Room Coverage: 132.1° Horizontal x 82.2° Vertical

Speakers
Drivers: Two 70mm (2.7")
Output: 90dB SPL @1W, 99dB SPL @8.0W, both +/-2dB at ½ meter
Sensitivity: 90+/-3dB SPL at 1W, ½ meter
THD: 1kHz < 2%
Speaker sampling rate: 48 kHz

Microphones
Frequency response: 90Hz ● 16kHz
Sensitivity: >-36dBFS +/-1dB @ 1Pa
Microphone data rate output: 48 kHz
Pickup range: 4.5m/15 ft
Beamforming elements: Six omnidirectional digital MEMS microphones forming five adaptive acoustic broadside beams
Audio processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector)
Noise suppression: AI filter
Add-on Mics: Supports up to 3 additional Rally Mic Pods for larger conference rooms

TECHNICAL SPECS

RightSense™ Technologies
RightLight™ with WDR: Renders natural skin tones for each participant.
RightSight™: Maintains persistent room awareness and detects human figures to auto-frame participants.
RightSound™: Distinguishes speech from other sounds to auto-level voices while suppressing background noise and echo.

Interfaces
HDMI Out: 2
HDMI In: 1
USB 3.0: Type A (3), Type C (1)
Network: 10/100/1G Ethernet
WiFi: 802.11a/b/g/n/ac (MIMO)
External Mic Input: Yes (proprietary input supports optional Rally Mic Pod, Rally Mic Pod Hub, and Rally Mic Pod Extension Cable)
Remote Control: Bluetooth® Low Energy

Power & Cables
Power Supply: Auto-sensing
Operating voltage/power: 100-240V, 19V, 4.74A
Power Supply Dimensions: 127mm x 51mm x 30mm
DC Cable: 1.5m / 4.9 ft
AC Cable: 1m / 3.28 ft
HDMI 1.4 cable: 2m / 6.5 ft
USB A to USB C 3.0 cable: 2.2m / 7.2 ft

Environmental
Operating Temperature: 0 to 40 °C
Storage Temperature: -40 to 70 °C
Humidity: 10 to 95%
BTU/hr: 57 idle, 64 in meeting

Security
Full Disk Encryption: AES-128
Data Encryption: Symmetric Keys, PKI
Device Identity: Protected by device attestation
Device Access: Authenticated using API
Key Protection: Arm TrustZone, RPMP

Guarantee
Standard: 2-year limited hardware guarantee included
Extended: Additional one-year extended guarantee available at the time of hardware purchase. Contact your reseller for availability.

Accessories
Mounts: Wall Mount for Video Bars, TV Mount for Video Bars
Audio: Rally Mic Pod, Rally Mic Pod Hub, Rally Mic Pod Mount, Rally Mic Pod Extension Cable
Connectivity: Logitech Strong USB (10m, 25m, 45m)
Touch Controller: Logitech Tap