

Wireless Sharing, Efficient Presentation with One-Press

The Yealink PA20 is a new 4K Ultra HD presentation assistant. Empowered with up to 4K/30FPS UHD hardware encode streaming output, PA20 saves a lot of effort by eliminating any software or driver installation. A USB Type-A/full-featured USB Type-C port is suitable for different computers and phones. Since PA20 has the embedded meeting assistant software and Wi-Fi 6 chip, simply plug PA20 into the devices, and you can quickly ready to present. PA20 provides you with a more convenient and richer content sharing experience.



One-Press Presenting



Plug-and-play



4K UHD



Wi-Fi 6 Chip



Extended Display Casting



Hardware Encoding



Intuitive Remote Control



High Security Encryption

Key Features and Benefits

4K HD Presentation, Low Latency

Thanks to the high-performance 2x2 MIMO, Wi-Fi 6 module, PA20 delivers immediate response, smooth and trouble-free presenting experience with low latency. PA20 supports a 2.4GHz/5GHz dual-band wireless network, perfect anti-interference capability, and up to 4K/30fps ultra HD presentation.

No Extra Driver, Plug-and-play

PA20 is suitable for the devices that support free collaboration and have full-featured USB Type-C port. PA20 adopts the built-in hardware encoding chip solution. No need to install any software or driver, and no CPU-occupied.

- Self-built Wi-Fi Network
- 4K/30fps Full HD Content Sharing
- Adaptive Software/Hardware Encoding
- Supports Dual-band 2.4GHz/5GHz Wireless Networks
- Plug and Play, without Extra Software or Driver
- AES & WPA Data Encryption

PA20 Specifications

Basic	Decoder	Up to 4k/30fps
	Input Power	5V/600 mA
	Power Consumption	2.2 W (Typical)
	Interface	- Full-featured USB Type-C×1 - USB-C to USB-A Adapter x1
	Button	START/STOP Button x 1
	LED	4K/UHD Indicator ×1 - System Error Indicator×1 - System Status Indicator×1
Wi-Fi	Standard	Wi-Fi 6, 802.11 a/b/g/n/ac/ax
	Frequency	2.4 GHz/5 GHz
	Encryption	WPA-PSK/WPA2-PSK
Bluetooth	Standard	Bluetooth 5.1
Advanced Features	Desktop Sharing	- Duplicated Display - Extended Display
	Collaboration	- Annotation - Intuitive Remote Control - Only IWB/Roomcast
Operating Environmental	Temperature range	-10 to 40°C
	Humidity	0 to 95%, non-condensing
Dimensions	Weight (g/lb)	75 g (0.165 lb)
	Size (mm/in)	220 mm × 38 mm × 16 mm (8.66" x 1.50" x0.63")

*The functions used with different endpoints are different. For details, please refer to support.yealink.com.

About Yealink

Yealink (Stock Code: 300628) is a global-leading provider of Unified Communication & Collaboration Solutions specialized in video conferencing, voice communications, and collaboration, dedicated to helping every person and organization embrace the power of “Easy Collaboration, High Productivity”.

With best-in-class quality, innovative technology, and user-friendly experiences, Yealink is one of the best providers in more than 140 countries and regions, ranks No.1 in the global market share of IP Phone, and is the Top 5 leader in the video conferencing market (Frost & Sullivan, 2021).

Copyright

Copyright © 2022 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

Copyright © 2022 Yealink(Xiamen) Network Technology CO., LTD. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (<http://support.yealink.com/>) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (<https://ticket.yealink.com>) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Web: www.yealink.com
Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District,
Xiamen, Fujian, P.R.C
Copyright©2022 Yealink Inc.All right reserved.